

Activator

Low Viscosity
 Ready to Use
 Low Odor
 100% Acrylic
 Excellent Bonding

COLOREDCRETE ACTIVATOR

Description:

- Low viscosity emulsion developed specifically for enhancing the strength, Durability and adhesion of cement-based products.
- Suitable for the formulation of conventional and lightweight renders and coatings, waterproofing systems, patching and repair mortars, underlayments and commercial flooring.
- Low-odour formulation ensures reduced worker discomfort during mixing and installation.
- Formulated systems display the typical "100% acrylic" benefit on exterior exposure: no degradation or colour development.

Use:

- Coloredcrete activator is used as primer, water proofing and bonding agent in Render, mortar, light weight coating, patching, scratch coats and number of coloredcrete products such as Spray-o-crete and Adcrete.

Mixing

- Coloredcrete Activator is normally used in mixture with potable water.
- Ratio of Activator to water may vary depending to the product and its usage.

Mixing Ratio

Type	Mixing Ratio with Water
Floor	1-1 Water
Wall	1-2 Water
Mortar	2% - 25% of Water Content
Patching	1-1 Water
Primer	1-1 Water

Packaging

- 20 Liters

Storage

- Store in cool and covered areas.
- Shelf Life: 12 months from manufacturing date.