

- Antislip
- Water Resistant
- Flexible
- No Shrinkage
- Indoor/Outdoor
- Wall/Floor

DESCRIPTION:

- Coloredcrete Spray-o-Crete is high performance concrete coaters with a unique combination of hardness, flexibility, wear resistance antislip, no sagging, no shrinkage, which enable seamless application and indoor & outdoor application.
- Coloredcrete Spray-o-Crete is an advanced, professional grade, two component, mineral base product that can be applied evenly on the substrate.
- Coloredcrete Spray-o-crete gives you architectural freedom to choose the color & the texture you desire.
- Spray-o-Crete is easy to apply using mortar gun.

APPLICATION:

- Coloredcrete Spray-o-Crete is used for new & old domestic & commercial wall & floors.
- It can be used in sidewalk, driveways, pool decks, wall, plasters, benches, stairs, & anywhere use have concrete.

TECHNICAL DATA:

Description	Value
Mixing	ratio 20kg ponds and to 2L water 2L activator
Application Temp.	10-30°C
Thickness	2-4 mm per layer
Coverage	3 m2 / 20kg / 3mm
Open Time	Approx. 15-30 min
Light Traffic	48 hours
Fully Loaded	7 days

SUBSTRATE PREPARATION

Prior to application, ensure that the surface is stable and has sufficient surface tensile strength. The surface should also be dry or slightly damp, clean, and free from dust and loose particles.

Mechanical surface preparation e.g. shot blasting or grinder is recommended. Deeper cracks, holes and other defects must be repairing with patching compound the surface should be permanently vibration free and crack free. Existing cracks in the floor base must be repaired professionally prior to the application of spray-o-Crete.

Apply a further layer of primer if necessary. Reapplication of the primer must be done within 1-2 hours of the first application.

Spray-o-Crete can be applied upon drying of the primer. To obtain uniform appearance and coloring the surface should be pre leveled and even.

MIXING & APPLICATION:

Place activator water in a plastic pail & grade walls add the spray-o-Crete powder while mixing, using a paddle mixer with variable speed: for 2-3 minutes until desired consistency is achieved.

Apply Spray-O-Crete in 2 coats:

1st coat may be troweled and 2nd coat sprayed, using mortar gun.

Allow 24-48 hours before sealer: using 2 coats of coloredcrete sealer (Make sure surface is clean & free from dust or dirt prior to application of the sealer)

SPECIAL PRECAUTIONS

The application must be protected from quick drying (due to either drafts or intense heat from the sun) for at least 12 hours. Concrete Slab or topping control joints must be followed.

TOOLS AND CLEANING.

Paddle mixer, trowel, spiked shoes, gauge rake or pin leveler. Mortar gun & mixer bucket should be washed with clean water and dried before and after application.

PRODUCTION, PACKAGING, STORAGE, SAFETY AND VALIDITY.

Spray-o-Crete is sold in 20kg bags.

Store bags and containers in a dry place and protected from extreme temperatures (best stored between 5-30°C) and direct sunlight. With the right conditions of storage, the product is valid for 12 months from the manufacturing date. There is no mandatory hazard labelling for spray-o-Crete. Avoid inhaling dust when opening packaging. Protect skin and eyes during the mixing process. Please refer to the material safety data sheet.

LIMITED WARRANTY:

Coloredcrete corporate warrants its material to be of good quality and, at its option, will replace or refund the purchase price of any material proven to be defective within one (1) year from date of manufacture. The above remedies shall be the limit of coloredcrete responsibility. Except for the foregoing, all warranties expressed or implied, including merchantability and fitness for a particular purpose, are excluded coloredcrete corporation shall not be liable for any consequential, incidental, or special damages arising directly or indirectly from the use of the materials.